



Sales Bulletin
Dec 2017

Valguard™ Conversion Varnish Vinyl Sealer - 550 VOC



Weight solids: 38%
Shelf Life: 18 months. 8-12 hour pot life @ 77°F once catalyzed
Catalyzation: 2.5 oz. per gallon with **CXC4000**

Air Dry to Sand/Recoat : 30-40 mins

<u>Code</u>	<u>Description</u>	<u>Size</u>	<u>List/ea</u>
4610-5	Vinyl Sealer, 550 VOC	5 Gal	\$ 283.66

Valguard™ Conversion Varnish
550 VOC



Valguard™ Conversion Varnishes are post-catalyzed, alkyd-amino varnishes and offer superior durability and UV protection. Ideal for kitchen and bath cabinets, tables and architectural millwork. Supplied ready to spray (after catalyzation). For professional use only.

Weight solids: 39.6-42%
Shelf Life: 18 months. 8-12 hour pot life @ 77°F once catalyzed
Catalyzation: 4 oz. per gallon with **CXC4000**

Air Dry to Sand/Recoat : 30-45 mins
78°, 50 RH

Conversion Varnish 550 VOC:

<u>Code</u>	<u>Description</u>	<u>Sheen</u>	<u>Gal size</u>	<u>List/ea</u>
5509-1	Gloss	90	1	\$ 59.82
5509-5	Gloss	90	5	285.11
5506-1	Semi-Gloss	60	1	59.82
5506-5	Semi-Gloss	60	5	285.11
5504-1	Soft Gloss	40	1	59.82
5504-5	Soft Gloss	40	5	285.11
5502-1	Satin	20	1	59.82
5502-5	Satin	20	5	285.11
5501-1	Matte	10	1	57.95
5501-5	Matte	10	5	285.11
4000.4000	Catalyst	-	1	82.43

- Surpasses all KCMA standards
- Self seal system or may be used with an approved companion sealer if desired
- Fast drying
- Ready to spray (after catalyzation)
- Outstanding flow and leveling