



New Sanders/Abrasives by SurfPrep

SPSS3X4 Sanding System



Specifications:

- Air - 16 SCFM / 3.1 CFM / 90 PSI
- RPM - Suggested Speed 10,000 RPM
- Orbit - 3mm perfect orbit
- Weight - 2 lbs.
- Height - 3.3"
- Length - 5.5"
- Material - Composite body, Steel Motor
- Size - 3" X 4" Footprint
- Power - .24 Horsepower / 179 Watts



SPBP3X4
Backup Pad

3" x 4" Orbital Air Sander

Low profile, compact footprint designed for use on flat surfaces, recessed corners, inside drawer boxes, & profiled moldings, etc. The lightweight nylon composite bodied sanders withstand rugged industrial applications and are excellent for both prep & finish sanding.

Code	Description	List/ea
SPS3X4	3" x 4" Orbital Sander, Hook & Loop, Non-Vacuum (sander only)	\$ 379.17
SPBP3X4	Backup Pad, 3" x 4", Hook & Loop, No hole	30.00
SPSS3X4	3" x 4" Sanding System	510.00

Sanding System includes the following:

SPS3X4 Sander, Variety Pack 3" x 4" Foam abrasives, Variety Pack 3" x 4" Film abrasives, 12' Swivel Air Hose & Tool Oil, 3" x 4" Pad Saver, 3" x 4" Interface Pad.

5" Trident 3/16" Random Orbital Air Sander

Designed with a durable composite body and are lightweight with a compact, recessed throttle lever. Ergonomically balanced for added comfort and control for the operator. Its cutting edge 'cooling fan' creates air flow around the counter balance spindle bearing which enhances the life of the tool. The Trident motor assembly is constructed of hardened steel for the cylinder and both end plates. A 360° swivel exhaust grate allows operator to redirect air flow.



SPTS5HL316

Specifications:

- Air - 17 SCFM / 3.1 CFM / 90 PSI
- RPM - Suggested Speed 12,000 RPM
- Orbit - 3/16 Random Orbit
- Weight - 1.84 lbs.
- Height - 3.9"
- Length - 7"
- Material - Composite body, Steel Motor
- Size - 5" Footprint
- Power - .28 Horsepower / 209 Watts



SPBP5
Backup Pad

Code	Description	List/ea
SPTS5HL316	5" Random Orbital Sander, Hook & Loop, Non-Vacuum	\$ 350.00
SPBP5HL	Backup Pad, 5", Hook & Loop, No hole	33.75
SPBP5PSA	Backup Pad, 5", PSA, No hole	33.75



SurfPrep Abrasives: Consistent finish, durable & long lasting


5" Film Discs, Hook & Loop



Aluminum Oxide Film backed abrasive discs are used for leveling & finish sanding. Provides consistent finish, faster cut, tear resistant edges, and overall longer life. Sacrificial stearate allows for minimal loading.

Code	Grit	Box Qty	List/bx
SP5HLF120	120	100 ea	\$ 70
SP5HLF150	150	100	65
SP5HLF180	180	100	65
SP5HLF220	220	100	65
SP5HLF320	320	100	65

5" PaperBack Discs, Hook & Loop



5" Paper Backed, Hook & Loop, Aluminum Oxide discs. Blended paper backing provides for enhanced support of grain and edge-wear. This premium abrasive grain in an open coat construction provides a true, consistent & uniform scratch. Innovative 'load-free' coating provides for a fast rate of cut and longer life.

Code	Grit	Box Qty	List/bx
SP5HLLPB080	80	100 ea	\$ 38
SP5HLLPB100	100	100	35
SP5HLLPB120	120	100	35
SP5HLLPB150	150	100	35
SP5HLLPB180	180	100	35
SP5HLLPB220	220	100	35
SP5HLLPB320	320	100	35

5" Film Discs, PSA



Aluminum Oxide Film backed abrasives are used for leveling & finish sanding. Provides consistent finish, faster cut, tear resistant edges, and overall longer life. Sacrificial stearate allows for minimal loading. PSA.

Code	Grit	Box Qty	List/bx
SP5PSAF080	80	100 ea	\$ 65
SP5PSAF100	100	100	65
SP5PSAF120	120	100	65
SP5PSAF150	150	100	60
SP5PSAF180	180	100	60
SP5PSAF220	220	100	60
SP5PSAF320	320	100	60

High Performance Foam Abrasives, Hook & Loop

Red Aluminum Oxide Foam Hook & Loop Pads for even cutting and flat sanding. A must use inside drawer boxes where manual hand sanding is a challenge or where discs sanders do not allow for full coverage into a corner. Can be used to sand detailed white wood beading on moldings. This pad will not load or pill.



5", 5-Hole Discs Sold per each, 25/ea per box.

Code	Grit	Holes	Thickness	List/ea
SPDF55R150.5	VF	5 Hole	5mm thin	\$ 1.54

3" x 4" Foam Pads Sold per each, 25/ea per box.



Code	Grit	Holes	Thickness	List/ea
SPRF5R100	F	No Hole	5mm thin	\$ 1.54
SPRF5R150	VF	No Hole	5mm thin	1.54
SPRF5R180	SF	No Hole	5mm thin	1.54
SPRF5R100.4	F	4 Hole	5mm thin	1.60
SPRF5R150.4	VF	4 Hole	5mm thin	1.60
SPRF5R180.4	SF	4 Hole	5mm thin	1.60
SPRF10R100.4	F	4 Hole	10mm firm	1.95
SPRF10R150.4	VF	4 Hole	10mm firm	1.95

Description		Finish/Scratch
F	Fine	220 - 240
VF	Very Fine	280 - 380
SF	Super Fine	450 - 600