



Specification	 <b>Dynapro 3D</b>	 <b>Dynapro 2.0</b>
Stated Load Capacity (Dynamic) ANSI / BHMA 156.9 grade 1	100 lb (45 kg)	90 lb (41 kg)
Heavy Duty Option	132 lb (60 kg), *110 lb (50 kg)	N/A
Standard Lengths	229mm (9") - 533mm (21")	229mm (9") - 533mm (21")
Extended Lengths	626mm (24"), 686mm (27"), 762mm (30")	N/A
Full Extension	Yes	Yes
Synchronization	Yes	Yes
Interchangeable cabinet interior length/CM	Yes	Yes
Interchangeable Drawer Box	Yes	Yes
12.7mm to 19mm Material	Yes	Yes
16 mm Version	Yes	Yes
19 mm Version	Yes	Yes
Side Tolerance +/-1.5 mm	Yes	Yes
Soft-close	Yes	Yes
Self-close	No	No
Mounting	FF, Euro	FF, Euro
Works with standard plastic rear sockets	Yes	Yes
Works with standard metal rear sockets	Yes	Yes
Corrosion resistant ANSI/BHMA finish test	Yes	Yes
Welded rear hook	Yes	Yes
Pull Open Force	20 N (4.5 lb)	30 N (6.75 lb)
Support Roller	Yes	Yes
Metal Drawer Box Option	**Yes - Vionaro	N/A
Min. Top Clearance	7	7
Drawer Bottom Recess	13	13
Bottom Minimal Mounting Height	27	27
38 mm Soft -close stroke length	No	Yes
1.5 mm Front Gap w/ 16mm Drawer Mat.	Yes	Yes
FLD interchangeable	Yes	Yes
FLD 3D adjust stable	Yes	Yes
FLD flange version	Yes	Yes
FLD none flange version	Yes	Yes
Narrow FLD	Yes	Yes
Height Adjustment	+ 3.5	+ 3.5
Side Adjustment	±1.5	±1.5
Depth Adjustment	+3 optional	+3 optional
Tilt Adjustment	+4 optional	N/A
Handle-free Opening	Dynapro Tipmatic, Sensomatic	N/A
	* Extended lengths (27" & 30"), 110 lb	
	**16mm 3D lengths 15" - 18" only	